

PathWay® Model 7208-CC DB15 A/B/C/D Switch with Contact Closure Remote

▪ Switching exclusively controlled by Remote Port!

INTRODUCTION:

The PathWay® Model 7208-CC DB15 Interface A/B/C/D Switch allows the user the capability of sharing a single DB15 interface device connected to the Common port among four other devices connected to the "A", "B", "C", and "D" ports. The Model 7208-CC is packaged in a slim desktop style enclosure.

There is no "local" or front panel switch controls on the unit. The Model 7208-CC can ONLY be switched remotely from the HD15(F) Contact Closure Control port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- Allows quick connection to any one of four devices from one COMMON device.
- **There is no "local" or front panel control.**
- HD15 (F) Remote Control port control unit via Contact Closure transition signals.
- The switch ports are transparent to all data.
- All (15) pins of the DB15 interface are switched via break-before-make electromechanical relays.
- The unit maintains last set position on power loss and continues to pass data.
- Upon power up, the unit switches based on the state of the Contact Closure.
- Remote Contact Closure control and status provides dry contact logic to allow the control of the switch position as well as obtain the present position.
- Front panel LED's display the present position and power status.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB15 cables available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (5) DB15 female connectors labeled A, B, C, D and COMMON.

DISPLAY: (5) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) HD15 female connector on rear panel accepts Contact Closure transition signals for Remote Control operation.

POWER: UL approved wall mount 100VAC-240VAC, 50Hz-60Hz power module supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug.

DIMENSIONS: Desktop Configuration, 7.75" W x 2.0" H x 7.25" D. (19.7 x 5.1 x 18.4 cm)

WEIGHT: Approximately 3.0 lbs. (1.0 kg)

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC-240VAC, 50Hz-60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

PathWay® Model 7208-CC DB15 A/B/C/D Switch Application with Exclusive Remote Control

