

LineSelect® Model 8470 DB25 THX Audio Interface A/B/C/D Switch, Rackmount, Manual Operation


- **Internal wiring between the switch and the DB25 port connectors utilizes twisted pairs to accommodate the pin/signal listing of THX audio signals. Pairing selected to minimize audio signal crosstalk.**

INTRODUCTION:

The *LineSelect*® Model 8470 DB25 THX Audio Interface A/B/C/D Switch allows the user to reroute data between any one of four DB25 devices to one COMMON device with the simple rotation of a selector switch. All 25 pins of the DB25 interface are switched. No need to plug and unplug interconnection cables thereby eliminating connector wear and/or errors when reconfiguring system connections. The *LineSelect*® Model 8470 is packaged in a compact enclosure that includes removeable brackets.

FEATURES:

- Ideal for THX Audio Interface switch applications.
- Allows quick connection to any one of four DB25 interface devices from one COMMON port.
- Manual operation via front-panel rotary switch.
- High quality sealed switch with self-wiping precious metal contacts.
- All (25) pins of the DB25 interface are switched via break-before-make rotary switch.
- All port shields are grounded to the chassis.
- Rear-panel chassis stud accepts spade lug for secure grounding.
- No external power required.
- **Packaging includes removeable brackets.**
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Ruggedized to withstand vibration encountered in mobile / motion applications.
- **Internal wiring is paired to minimize audio signal crosstalk for THX signal assignment at DB25 interface.**
- Lifetime warranty against manufacturing defects.
- Custom length, custom designed DB25 cables wired to your specifications available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (5) DB25 female connectors labeled A, B, C, D, and COMMON.

FRONT PANEL CONTROLS: (1) Rotary switch on front panel selects A, B, C, D.

POWER: No power required. Manually operated.

LOW IMPEDANCE CONTACTS: Typical contact resistance, 3 milliohms.

SIGNAL PAIRING: Each signal "positive" is paired with its respective signal "ground".

DIMENSIONS: With Brackets attached: 6.4" W x 3.5" H x 6.64" D. (16.3 x 8.9 x 16.9 cm)

WEIGHT: Approximately 2.0 lb. (0.9 kg).

LineSelect® MODEL 8470 DB25 THX Audio Interface A/B/C/D Application:

