



Electro Standards Laboratories
ADVANCED SYSTEMS DESIGN & SERVICES



SPECIFICATIONS
MODEL 9443R
(Cat. No. 309443R)

LineSelect® Model 9443R DB25 A/B Switch with Half Rack & Full Rackmount Enclosure, RoHS Compliant

- *Applicable to ANY DB25 Interface since all 25 pins switched.*
- *High Quality Manual Data Network Switches increase the reliability of your Network.*

INTRODUCTION

The **LineSelect®** Model 9443R Single Channel DB25 A/B Switch allows the user to switch COMMON equipment to either A or B ports with a simple turn of a rotary switch knob. The unit supports all 25 pins of the DB25 interface. No need to plug and unplug cables, thereby eliminating connector wear. The **LineSelect®** Model 9443R is enclosed in a desktop size enclosure with a 1U full rack size front panel, and an all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.



FEATURES:

- Allows quick connection to either Network A or Network B from one COMMON device.
- **Certified RoHS compliant.**
- High quality sealed switch with self-wiping low impedance contacts.
- All ports are transparent to all data.
- All 25 pins of the DB25 interface are switched via break-before make rotary switch.
- **DB25 female connectors used for the A, B, & COMMON ports.**
- Manually operated. No power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Lifetime warranty against manufacturing defects.
- Custom length DB25 cables available for your switch installation.

SPECIFICATIONS:

PORT CONNECTORS: (3) DB25 female connectors on rear panel labeled A, B, and COMMON.

FRONT PANEL CONTROL: (1) Rotary Switch on front panel selects A or B.

PINS SWITCHED: 25 pins switched.

MTBF: 3 15890 HRS.

POWER: No power required.

ENCLOSURE: Aluminum slim rackmount enclosure.

DIMENSIONS: 19" W x 1.75" H x 10.0" D.
(48.3 x 3.8 x 25.4 cm)

WEIGHT: Approximately 2.0 lbs. (0.9 kg)

- *Private Labeling Option: ESL switches may be Custom/Private Labeled. Ask for quote.*

LineSelect® Model 9443R DB25 A/B Switch Application: (Switches ANY DB25 Interface!)

