

SPECIFICATIONS MODEL 9473

(Cat. No. 309473)

LineSelect Model 9473 4-Channel RJ45 Cat6 A/B Switch, Simultaneous Control

Applicable to switching ANY RJ45 interface, quickly and reliably.

INTRODUCTION

The LineSelect® Model 9473 enables each of four RJ45 Cat6 Common ports to select either of two network LANs or devices, via A or B port RJ45 connectors. All four channels of the LineSelect® Model 9473 A/B Switch are switched simultaneously via rotary switch knob located on the front panel.

The unit supports all 8 pins of the RJ45 Cat6 interface. No need to plug and unplug cables thereby eliminating connector wear. The LineSelect® Model 9473 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.



FEATURES:

- Simultaneously switch all four channels of RJ45 A/B via front panel rotary switch knob.
- Tested for Cat6 compliance.
- All 8 pins of the RJ45 interface are switched via breakbefore-make rotary switch.
- High quality sealed switch with self-wiping low impedance contacts.
- Manually operated. No power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Rackmount configuration is standard.
- Lifetime warranty against manufacturing defects.

SPECIFICATIONS:

PORT CONNECTORS: (12) RJ45 female connectors, three labeled A, B, and COMMON, for each of the 4 channels.

FRONT PANEL CONTROL: (1) Rotary switch on front panel switches all 4 channels simultaneously.

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 1.75" H x 8.65" D.

(48.3 x 4.4 x 22.0 cm)

WEIGHT: Approximately 2.0 lbs. (0.9 kg)

Be sure to order the Cat6 patchcords at custom lengths to improve system performance.

